

IN THE CLAIMS

This listing of the claim will replace all prior versions and listings of claim in the present application.

Listing of Claims

1. (currently amended) A method of selecting an optimal set of antennas from a plurality of antennas for use by a transmitter ~~and/or~~ having a plurality of RF chains to transmit and/or receive a wireless signal on a wireless link, said method comprising the steps of:

determining, based on wireless signals on said wireless link received at a receiver, information concerning transmission of wireless signals on said wireless link,

wherein said information includes at least one of channel capacity, diversity, spatial multiplexing or any other criteria used to optimize the wireless link;

selecting, at said transmitter, an optimal set of antennas from said plurality of antennas based on said information,

wherein said optimal set of antennas is a set number of said plurality of antennas; and

connecting said RF chains to said optimal set of antennas to permit transmission ~~and/or reception~~ of said wireless signal from said RF chains on said wireless link via said optimal set of antennas,

wherein said RF chains correspond in number to the set number of antennas in said optimal set of antennas, and the number of antennas included in said plurality of antennas is greater than the number of RF chains.

Claim 2 (canceled).

3. (original) A method according to claim 1, wherein said determining step is performed at a receiver.

4. (original) A method according to claim 1, wherein said determining step is performed at said transmitter.

5. (currently amended) A transmitter comprising:
a plurality of antennas;
a plurality of RF chains, each RF chains transmits a wireless signal on a wireless link to a receiver via one of said plurality of antennas; and
an antenna selection apparatus which selects an optimal set of antennas from said plurality of antennas for use by said RF chains to transmit said wireless signal on said wireless link,

wherein said optimal set of antennas is a set number of said plurality of antennas,

wherein ~~said antenna selection apparatus determines information concerning~~ transmission of wireless signals on said wireless link is determined, based on wireless signals on said wireless link received at a receiver,

wherein said antenna selection apparatus selects an optimal set of antennas from said plurality of antennas based on said information, and connects said RF

chains to said optimal set of antennas to permit transmission of said wireless signal from said RF chains on said wireless link via said optimal set of antennas,

wherein said information includes at least one of channel capacity, diversity, spatial multiplexing or any other criteria used to optimize the wireless link, and

wherein said RF chains correspond in number to the set number of antennas in said optimal set of antennas, and the number of antennas included in said plurality of antennas is greater than the number of RF chains.

6. (currently amended)A transmitter-according-to-claim-5, comprising:

a plurality of antennas;

a plurality of RF chains, each RF chains transmits a wireless signal on a wireless link to a receiver via one of said plurality of antennas; and

an antenna selection apparatus which selects an optimal set of antennas from said plurality of antennas for use by said RF chains to transmit said wireless signal on said wireless link,

wherein said optimal set of antennas is a set number of said plurality of antennas,

wherein said antenna selection apparatus determines information concerning transmission of wireless signals on said wireless link, selects an optimal set of antennas from said plurality of antennas based on said information, and connects said RF chains to said optimal set of antennas to permit transmission of said wireless signal from said RF chains on said wireless link via said optimal set of antennas, and

_____ wherein said RF chains correspond in number to the set number of antennas in said optimal set of antennas, and the number of antennas included in said plurality of antennas is greater than the number of RF chains.

_____ wherein said receiver includes a plurality of antennas.

Claim 7 (canceled).

8. (original) A transmitter according to claim 5, wherein said information received by said antenna selection apparatus is determined at said transmitter.

9. (previously presented) A transmitter comprising:
a plurality of antennas;
a plurality of RF chains, each amplifier transmits a wireless signal on a wireless link to a receiver via one of said plurality of antennas; and
an antenna selection apparatus which selects an optimal set of antennas from said plurality of antennas for use by said RF chains to transmit said wireless signal on said wireless link,

wherein said optimal set of antennas is a set number of said plurality of antennas,

wherein said antenna selection apparatus receives information concerning transmission of wireless signals on said wireless link, selects an optimal set of antennas from said plurality of antennas based on said information, and connects

said RF chains to said optimal set of antennas to permit transmission of said wireless signal from said RF chains on said wireless link via said optimal set of antennas, and

wherein said RF chains correspond in number to the set number of antennas in said optimal set of antennas, and the number of antennas included in said plurality of antennas is greater than the number of RF chains.

10. (original) A transmitter according to claim 9, wherein said receiver includes a plurality of antennas.

11. (original) A transmitter according to claim 9, wherein said information is used to optimize said wireless link according to criterion including any one of capacity, diversity, spatial multiplexing and any other criterion for which the wireless link is to be optimized.

12. (original) A transmitter according to claim 9, wherein said information received by said antenna selection apparatus is determined at said receiver.

13. (currently amended) A receiver comprising:
a plurality of antennas;

a plurality of receive radio frequency (RF) chains, each receive RF chain receives a wireless signal on a wireless link from a transmitter via one of said plurality of antennas; and

an antenna selection apparatus which selects an optimal set of antennas from said plurality of antennas for use by said receive RF chains to receive said wireless signal on said wireless link,

wherein said optimal set of antennas is a set number of said plurality of antennas,

wherein ~~said antenna selection apparatus determines information concerning~~ receiving of wireless signals on said wireless link is determined, based on wireless signals on said wireless link received at a,

wherein said antenna selection apparatus selects an optimal set of antennas from said plurality of antennas based on said information, and connects said receive RF chains to said optimal set of antennas to permit receipt of said wireless signal from said receive RF chains on said wireless link,

wherein said information includes at least one of channel capacity, diversity, spatial multiplexing or any other criteria used to optimize the wireless link, and

wherein said receive RF chains correspond in number to the set number of antennas in said optimal set of antennas, and the number of antennas included in said plurality of antennas is greater than the number of said receive RF chains.

14. (currently amended) ~~A receiver according to claim 13, comprising:~~

a plurality of antennas;

_____ a plurality of receive radio frequency (RF) chains, each receive RF chain receives a wireless signal on a wireless link from a transmitter via one of said plurality of antennas; and

_____ an antenna selection apparatus which selects an optimal set of antennas from said plurality of antennas for use by said receive RF chains to receive said wireless signal on said wireless link,

_____ wherein said optimal set of antennas is a set number of said plurality of antennas,

_____ wherein said optimal set of antennas is a set number of said plurality of antennas,

_____ wherein said antenna selection apparatus determines information concerning receiving of wireless signals on said wireless link, selects an optimal set of antennas from said plurality of antennas based on said information, and connects said receive RF chains to said optimal set of antennas to permit receipt of said wireless signal from said receive RF chains on said wireless link, and

_____ wherein said receive RF chains correspond in number to the set number of antennas in said optimal set of antennas, and the number of antennas included in said plurality of antennas is greater than the number of said receive RF chains,

_____ wherein said transmitter includes a plurality of antennas.

Claim 15 (canceled).

16. (original) A receiver according to claim 13, wherein said information received by said antenna selection apparatus is determined at said receiver.

17. (previously presented) A receiver comprising:

- a plurality of antennas;
- a plurality of receive radio frequency (RF) chains, each receive RF chain receives a wireless signal on a wireless link from a transmitter via one of said plurality of antennas; and
- an antenna selection apparatus which selects an optimal set of antennas from said plurality of antennas for use by said receive RF chains to receive said wireless signal on said wireless link,

wherein said optimal set of antennas is a set number of said plurality of antennas,

wherein said antenna selection apparatus receives information concerning transmission of wireless signals on said wireless link, selects an optimal set of antennas from said plurality of antennas based on said information, and connects said receive RF chains to said optimal set of antennas to permit receipt of said wireless signal from said receive RF chains on said wireless, and

wherein said receive RF chains correspond in number to the set number of antennas in said optimal set of antennas, and the number of antennas included in said plurality of antennas is greater than the number of said receive RF chains.

18. (previously presented) A receiver according to claim 17, wherein said transmitter includes a plurality of antennas.

19. (previously presented) A receiver according to claim 17, wherein said information is used to optimize said wireless link according to criterion including any one of capacity, diversity, spatial multiplexing and any other criterion for which the wireless link is to be optimized.

20. (previously presented) A receiver according to claim 17, wherein said information received by said antenna selection apparatus is received by said receiver.

21. (currently amended) A transmitter comprising:
a plurality of antennas;
a plurality of RF chains, each RF chain transmits a wireless signal on a wireless link to a receiver via one of said plurality of antennas; and
an antenna selection apparatus which selects an optimal set of antennas from said plurality of antennas for use by said RF chains to transmit said wireless signal on said wireless link,
wherein said optimal set of antennas is a set number of said plurality of antennas,

wherein ~~said antenna selection apparatus determines information concerning~~
transmission of wireless signals on said wireless link is determined, based on
wireless signals on said wireless link received at a,
wherein said antenna selection apparatus determines an optimal number of
antennas based on said information, selects an optimal set of antennas from said
plurality of antennas according to said optimal number of antennas determined
based on said information, and connects said RF chains to said optimal set of
antennas to permit transmission of said wireless signal from said RF chains on said
wireless link via said optimal set of antennas,

wherein said information includes at least one of channel capacity, diversity,
spatial multiplexing or any other criteria used to optimize the wireless link, and

wherein said RF chains correspond to a number at least equal to a highest
possible optimal number of antennas to be determined based on said information,
and the number of antennas included in said plurality of antennas is greater than the
number of RF chains.

22. (currently amended) ~~A transmitter according to claim 21 comprising:~~
a plurality of antennas;
a plurality of RF chains, each RF chain transmits a wireless signal on a
wireless link to a receiver via one of said plurality of antennas; and
an antenna selection apparatus which selects an optimal set of antennas from
said plurality of antennas for use by said RF chains to transmit said wireless signal
on said wireless link,

wherein said optimal set of antennas is a set number of said plurality of antennas,

wherein said antenna selection apparatus determines information concerning transmission of wireless signals on said wireless link, determines an optimal number of antennas based on said information, selects an optimal set of antennas from said plurality of antennas according to said optimal number of antennas determined based on said information, and connects said RF chains to said optimal set of antennas to permit transmission of said wireless signal from said RF chains on said wireless link via said optimal set of antennas, and

wherein said RF chains correspond to a number at least equal to a highest possible optimal number of antennas to be determined based on said information, and the number of antennas included in said plurality of antennas is greater than the number of RF chains,

wherein said receiver includes a plurality of antennas.

Claim 23 (canceled).

24. (previously presented) A transmitter comprising:

a plurality of antennas;

a plurality of RF chains, each amplifier transmits a wireless signal on a wireless link to a receiver via one of said plurality of antennas; and

an antenna selection apparatus which selects an optimal set of antennas from said plurality of antennas for use by said RF chains to transmit said wireless signal on said wireless link,

wherein said optimal set of antennas is a set number of said plurality of antennas,

wherein said antenna selection apparatus receives information concerning transmission of wireless signals on said wireless link, determines an optimal number of antennas based on said information, selects an optimal set of antennas from said plurality of antennas according to said optimal number of antennas determined based on said information, and connects said RF chains to said optimal set of antennas to permit transmission of said wireless signal from said RF chains on said wireless link via said optimal set of antennas, and

wherein said RF chains correspond to a number at least equal to a highest possible optimal number of antennas to be determined based on said information, and the number of antennas included in said plurality of antennas is greater than the number of RF chains.

25. (previously presented) A transmitter according to claim 24, wherein said receiver includes a plurality of antennas.

26. (previously presented) A transmitter according to claim 24, wherein said information is used to optimize said wireless link according to criterion including

any one of capacity, diversity, spatial multiplexing and any other criterion for which the wireless link is to be optimized.